

## Extensometer



ATEX 

### FEATURES

- Strain gage based sensor
- Alloy steel construction
- 2 bolt holes
- IP66 Hermetically sealed protection

### OPTIONAL FEATURE

- EEx ia IIC T4 hazardous area approval

### DESCRIPTION

The Model 178 extensometer is a load sensor designed for force measurement on any load-bearing structure. This extensometer provides the total solution for weighing, level control, stress and fatigue monitoring. The design also allows multiple sensors to be permanently mounted for more complex stress profiling and analysis.


The Model 178 extensometer provides an ideal solution for non-intrusive level measurements for materials that are

subject to uneven buildup, bridging, or sidewall collection. Also, liquids or wetted materials that are not suited for direct contact level measurement are an ideal application for the Model 178 extensometer. The design of the Model 178 makes it an excellent solution for retrofitting existing structures without compromise of the integrity of the vessel or structure.

### APPLICATIONS

- Tank weighing or level systems
- Agricultural equipment
- Rolling mill sensing
- Moment sensing
- Structural loading measurements
- Bridge structures

### OUTLINE DIMENSIONS in mm



Extensometer

<b>SPECIFICATIONS</b>		
<b>PARAMETER</b>	<b>VALUE</b>	<b>UNIT</b>
Calibrated output	1.7	mV/V at 500 $\mu\epsilon$
Overload capability (zero)	300	% of rated output
Overload capability (max)	500	% of rated output
Input resistance	350 $\pm$ 10	$\Omega$
Output resistance	350 $\pm$ 10	$\Omega$
Insulation resistance	>2000	M $\Omega$
Excitation, recommended	10	Vdc
Excitations, range	5-20	Vdc
Thermal effect on zero	0.025	$\pm$ % of FSO/ $^{\circ}$ C
Compensated temperature range	-30 to +80	$^{\circ}$ C
Construction	Painted steel	
Environmental protection	IP66	

## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.